



DURABODY CERAMIC
More Dense. More Durable. More Designs.

THE CERAMIC THAT THINKS IT'S PORCELAIN

Durabody ceramic tiles are made to last a lifetime, while looking like the day they were installed. That's a lifetime of muddy paws, stomping children, cold snaps and everything else life can throw at it. The Durabody secret? Our tiles are fired at the same temperature and glazed just like porcelain. That means you get virtually the same frost resistance, water resistance and durability as porcelain at a fraction of the cost. And with designs to match your taste, Durabody tiles will make any space beautiful—inside or out.

LUMEN FX

CRAFTED FOR EFFECT

Interceramic brings digitally printed tiles a step closer to reality with LumenFX. This special process replicates the infinite beauty found in nature by adding distinct and specific highlights to each individual tile. The unique ink creates depth to your space by adding the right touch of reflectivity to the tile's design. Get the beauty of nature and the durability of tile with LumenFX from Interceramic.

USAGE INFORMATION

TILE APPLICATIONS	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Floors	•	•	•
Walls/Backsplashes	•	•	•
Countertops	•	•	•
Exterior	•	•	•

PLEASE NOTE: Not recommended for ramps or floor areas exposed to water or heavy grease accumulation.

TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM #
Abrasion Resistance (PEI)	Class III	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	≥50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	>0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	8.0	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>350 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484
Recycled Content (Pre-Consumer)	19.20%	N/A	N/A
Recycled Content (Post-Consumer)	11.40%	N/A	N/A

*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials; the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.



interceramicusa.com



WHEELHOUSE

Durabody Ceramic Floor Tile

Interceramic®
CRAFTED FOR LIFE

WHEELHOUSE

Durabody Ceramic Floor Tile



Patina



Breech




Compass



DECORATIVE ACCENTS



12"x12"
Box Mosaic




12"x12"
Box Mosaic



12"x12"
Box Mosaic


SIZES



12"x24"
Up to 25 Faces



16"x16"
Up to 25 Faces



3"x12"
Bullnose

TRIM (Available in all colors)



Variation Rating: SUBSTANTIAL
Substantial shade and texture variation with in each carton.

