



TILE TECHNICAL DATA

Wall Tile

| Series | Trim Available | Shade/Texture Spectrum (STS) Rating | Water Absorption | Breaking Strength | Bonding Strength | Crazing Resistance | Recycle Content | Wall Tile Thickness |
|----------------------|----------------|-------------------------------------|------------------|-------------------|------------------|--------------------|-----------------|----------------------------------------|
| ANSI Designation | | | ASTM C373 | ASTM C482 | ASTM C482 | ASTM C424 | | |
| ANSI Standard | | | <20% | ≥90 lbs | ≥50 psi | Resistant | | |
| Alma Natura | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 17% | 8x12 = 7.7-8.1mm 4½x8½ = 7.3-7.1 |
| Aquarelle | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 10% | 8.15 mm |
| Brick | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | N/A | 7.3-7.7 mm |
| Bruselas | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 10% | 7.45 mm |
| Cellar | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 18% | 7.3-7.7 mm |
| Essentials | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | 17% | 9.1-9.3 mm |
| Lipstick (Exterior) | Yes | V1 | <3.00% | >450 lbs | N/A | N/A | 35.2% | 7.3-7.9 mm |
| Lipstick (Interior) | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | 41.6% | 6x6 = 7.1-7.3 mm 4½x4½ = 7.3-7.5 mm |
| Marbre | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 18% | 7.3-7.7 mm |
| Milan | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | N/A | 7.1-7.6 mm |
| Montreaux | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 10% | 7.45 mm |
| Oxide | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 10% | 7.45 mm |
| Pinot | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 17% | 7.3-7.7 mm |
| Puebla | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 10% | 7.45 mm |
| Spa | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | 10% | 8.15 mm |
| Structura | No | V3 | <20% | >150 lbs | >50 psi | Resistant | 18% | 7.3-7.7 mm |
| Taberna | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 18% | 7.3-7.7 mm |
| Tessuto | Yes | V2 | <20% | >150 lbs | >50 psi | Resistant | 17% | 7.3-7.7 mm |
| Up & Down | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | N/A | Up= 9.9 mm Down = 7.1 mm |
| Urbane | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 18% | 7.3-7.7 mm |
| Vesubio | Yes | V3 | <20% | >150 lbs | >50 psi | Resistant | 15% | 8.8-9.1 mm |
| Wall Tile Collection | Yes | V1 | <20% | >150 lbs | >50 psi | Resistant | 10% | 7.45 mm |