



USAGE INFORMATION

TILE APPLICATIONS	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Floors	•	•	•
Walls/Backsplashes	•	•	•
Countertops	•	•	•
Exterior	•	•	•

PLEASE NOTE: Not recommended for ramps or floor areas exposed to water or heavy grease accumulation.

TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM #
Abrasion Resistance (PEI)	Class IV	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	>50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	>0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	7.5	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>400 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484

*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials; the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.



interceramic.com



SUNWOOD PRO
High Density Glazed Ceramic Floor Tile

Interceramic®
CRAFTED FOR LIFE

SUNWOOD PRO

High Density Glazed Ceramic Floor Tile

HIGH DENSITY CERAMIC

Suitable Rooms



Legend Beige



Centennial Gray



Cowboy Brown



SIZES



7"x36"



Variation Rating: HIGH
High shade and texture variation with in each carton

LEGEND BEIGE & COWBOY BROWN



CENTENNIAL GRAY



LEGEND BEIGE

