

tessuto



www.interceramic.com



Ecrú Gray, Basalto Black

tessuto

With the help of state of the art technology, the elegance of natural fabric is captured in Tessuto floor & wall tile. This textile replication offers a refreshing yet welcoming environment, with its soft appeal of rich linen.



tesuto



Ideal for all residential and most commercial floor and wall applications.

Glazed Porcelain Floor and Glazed Ceramic Wall Tile
STS M • PEI IV



Tan Beige, Cutch Brown

Colors

Floor



Pearl White



Tan Beige



Cutch Brown




Ecru Gray



Basalto Black


Floor Size



12 x 24 in

Floor Trim

Available in all colors



Surface Bullnose
3 x 12 in

Wall



Pearl White



Tan Beige



Cutch Brown




Ecru Gray



Basalto Black

Wall sizes




8 x 12 in



4 1/4 x 8 1/2 in

Wall Trim


available in all colors



Surface Bullnose
2 1/2 x 8 in




Surface Bullnose
Corner
2 1/2 x 2 1/2 in



Surface Bullnose
S4489
4 1/4 x 8 1/2 in



Surface Bullnose
Corner Exterior
SN4449
4 1/4 x 4 1/4 in



Radius Bullnose
A4200
2 x 6 in



Radius Bullnose
Corner Exterior
AN4200
2 x 2 in



Tan Beige, Cutch Brown

Testing Results

Floor

Wear Rating	IV P	EI
Coefficient of Friction	>0.60 A	STM C1028
Water Absorption	<0.50% A	STM C373
Scratch Hardness 8	.0 M	OHS Scale
Breaking Strength	430 lbs	ASTM C648
Frost Resistance R	esistant A	STM C1026
Recycle Content	20% N	/A
Thickness	10.8 mm N	/A

Wall

Water Absorption	15-20% A	STM C3737
Breaking Strength	>150 lbs	ASTM C648
Chemical Resistance R	esistant A	STM C650
Bonding Strength	>50 psi A	STM C482
Crazing Resistance R	esistant A	STM C424
Recycle Content	17% N	/A
Thickness 7	.3 - 7.7 mm	N/A

LEED Information



For more information about qualifying LEED points please visit:

www.interceramicgreen.com

