



USAGE INFORMATION

TILE APPLICATIONS	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Floors	•	•	•
Walls/Backsplashes	•	•	•
Countertops	•	•	•
Exterior	•	•	•

PLEASE NOTE: Not recommended for ramps or floor areas exposed to water or heavy grease accumulation.

TECHNICAL INFORMATION

TEST	RESULTS	ANSI STANDARDS	ASTM #
Abrasion Resistance (PEI)	Class IV	Class 0-V	ASTM C1027
Chemical Resistance	Resistant	As Reported	ASTM C650
Bonding Strength (psi)	>50 psi	>50 psi	ASTM C482
Dynamic Coefficient of Friction (DCOF)*	>0.42	As Reported	ANSI A 137.1-2012
Scratch Hardness	7.0	MOHS 1-10	MOHS Scale
Water Absorption	<3.0%	3.0% - 7.0%	ASTM C373
Breaking Strength	>400 lbf.	>250 lbf.	ASTM C648
Frost Resistance	Resistant	As Reported	ASTM C1026
Stain Resistance	Resistant	As Reported	ASTM C1378
Crazing Resistance	Resistant	As Reported	ASTM C424
Thermal Shock	Resistant	As Reported	ASTM C484

*It is important to note that Dynamic Coefficient of Friction results can vary after installation due to the presence of foreign materials, such as water, oil and other materials; the length of the human stride at the time of slip; type of floor finish and condition of shoe sole.



interceramic.com



TIRRENI

High Density Glazed Ceramic Floor Tile

Interceramic®
CRAFTED FOR LIFE





TIRRENI

High Density Glazed Ceramic Floor Tile



Suitable Rooms



Cenere



Recommended Grout Colors
Custom 335 Winter Gray
Laticrete 60 Dusty Gray

Terra




Recommended Grout Colors
Custom 185 New Taupe
Laticrete 60 Dusty Gray

Fuoco




Recommended Grout Colors
Custom 52 Tobacco Brown
Laticrete 43 Chocolate Truffle

SIZES



16"x16"

TRIM (Available in all colors)



4"x16"
Bullnose



Variation Rating: HIGH
High shade and texture
variation with in each carton

